



## DilliGent<sup>®</sup> ScaleTec

No more limescale problems!  
No chemicals or electricity required

# Steinhardt DilliGent® ScaleTec

No more limescale problems!  
No chemicals or electricity required



## The Challenge

### Limescale deposits in piping, taps, hot-water boilers and all water-circulating systems

Hard limescale deposits often spell the end of service for many taps, water-circulating machines and systems. Over time limescale deposits build up in pipework too and inhibit the free water flow. Additionally, hot-water boilers or industrial systems affected by this problem consume considerably more energy or electricity and this results in higher operating costs. Costly repair work or replacement equipment are often required; particularly in hard-water areas this problem is all too common.



© Fotolia.com/Pixelot

## The Solution

The **DilliGent®** ScaleTec with its environmentally-friendly, physical water treatment provides the answer. The compact **DilliGent®** ScaleTec units are connected to existing cold and/or hot water cycles and operate on the throughflow principle. The unit's capacity depends on the dimensions of the existing system.



*No limescale deposits thanks to the physical DilliGent® ScaleTec hardwater stabiliser – environmentally-friendly, no chemicals and no electricity required*

## The Way

The **DilliGent®** ScaleTec is an environmentally friendly water treatment technology based on extremely powerful catalysts. As the water flows through the catalysts, the water ions change direction. The calcium crystals lose their natural bonding force and so **cannot form solid limescale deposits**. The treatment does not affect the high quality of your drinking water.

A further benefit is the decrease of water surface tension. The installation of the **DilliGent®** ScaleTec **reduces the quantity of detergent and cleaning products** required.

The **DilliGent®** ScaleTec units require no electrical connection, they are quick and easy to mount, have a long service-life and are completely maintenance-free.

### Performance values

Type	Connection	Capacity
DN-10	3/8"	0,2 m³/h
DN-15	1/2"	0,7 m³/h
MIDI	3/4"	1,6 m³/h
DN-20	3/4"	2 m³/h
DN-25	1"	4 m³/h
DN-32	1 1/4"	8 m³/h
Set for SFH	1 x 3/4"; 1 x 1/2" for cold and hot water	
Set für MFR	1 x 1"; 1 x 1/2" for cold and hot water	
Industrial standard		
DN-40	1 1/2"	12 m³/h
DN-50	2"	20 m³/h
DN-65	2 1/2"	37 m³/h
DN-80	3"	55 m³/h

### The Advantages

- safe, sustainable prevention of limescale
- breakdown of existing limescale deposits
- hard water stabilisation without chemicals
- no mineral loss in the water
- environmentally-friendly
- low space requirement, easy installation
- maintenance-free, no operating or incidental costs
- long-life technology
- no electricity required

© Foto Frontpage left in the middle: Fotolia.com/Bernd Leitner

© Steinhardt GmbH · Schutzvermerk ISO 14001 beachten / Änderungen vorbehalten / Stand 01/2022